

Soils

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

90
SHUTTLE XL



4 CYLINDER STAGE V
HIGH END TORQUE ENGINE

SYNCHRO SHUTTLE
TRANSMISSION

ADVANCED HYDRAULIC
LIFT CAPACITY

S COMMAND
CENTER

MULTIPLE
TYRE OPTIONS



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

THE TOUGHEST
PERFORMER
« FOR YOUR FIELD »

90
SHUTTLEXL

Solis



FEATURES	90 SHUTTLEXL
ITL ENGINE	
No. of cylinders / capacity (cc) / emissions level	4/ 4087/ CRDi Stage V
After treatment system	DOC + DPF + SCR (Ad Blu)
Rated engine power (kw/Hp)	67.3/90
Rated engine speed	2200
Max. torque (Nm)	375@1400 Rpm
Aspiration	Turbo charged
Intercooler	●
Air Cleaner	Dual Stage Dry Type
Block Heater	○
Updraft Exhaust Pipe	●
Downdraft Exhaust Pipe	○
Fuel tank capacity (L)	110
DEF Tank capacity (L)	12
TRANSMISSION	
12x12 Synchro Shuttle transmission (4WD)	●
Minimum forward speed	1.22kmph
Maximum forward speed	35kmph
20x20 Synchro Shuttle transmission (4WD) with Super Creeper	○
Minimum forward speed	0.25kmph
Maximum forward speed	40kmph
FRONT AXLE	
4WD Front Axle	●
Differential Lock	Mechanical
4WD Actuation	Electro Hydraulic
Brake Actuation	Hydraulic Assisted
PTO	
PTO Type	Mechanical
540/540E	●
540/1000	○
540/ground speed	○
HYDRAULIC	
Hydraulic pump flow (lpm)	65
Draft Control	●
Liftomatic system	●
Lift Capacity	3000 Kg / 3500 Kg (0)
Linkage Category	II
Self Locking Linkages	○
Max. no. of rear remotes	2/3 (0)
Max. no. of Mid remotes	○

● Standard ○ Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

FEATURES	90 SHUTTLEXL
Mechanical joystick control for mid mounts with valves	○
REAR HITCHES	
E-Mark Swinging Drawbar	●
Semi Automatic Ladder Hitch	○
Automatic Ladder Hitch	○
Cuna Type Ladder Hitch	○
TRAILER BRAKES	
Without Trailer Brakes	●
Hydraulic Trailer Brakes	○
Dual Line Pneumatic Trailer Brakes	○
ELECTRICALS (ROPS/CAB)	
Battery	130AH 800CCA
Alternator	120A
Button Operated Battery Cut off Switch, 3 Pinsocket, Seven On Trailer Socket	●
OPERATOR ENVIRONMENT	
Suspended platform (with ROPS)	●
Premium Driver seat	○
Tiltable & Telescopic Steering	○
Integrated Loader Joystick	○
Cabin Air Conditioning (With Cabin)	○
DIMENSIONS (ROPS/CAB)	
Wheelbase (mm)	2350
Overall Height (mm)	2700-2720
Overall Width (mm)	2030-2050
Overall Length (mm)	3985-4205
Front Track Width (mm)	1675
Rear Track Width (mm)	1510
Ground Clearance (mm)	370
Unladen Mass (Kg)	4035
Tyre Combination	12.4x24 & 18.4x30
OPTIONAL TYRE COMBINATIONS	
Bias Tyres (4WD)	13.6*24 16.9*34
Radial Tyres (4WD)	320/85R24 & 460/85R30 320/70R24 & 480/70R30 360/85R24 & 460/85R30 420/65R24 & 540/65 R34

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com